

**WORKING PRESSURE CHART**  
**PARKER HOSE SIZE / RECOMMENDED MAXIMUM WORKING PRESSURES**

In addition to pressure, other factors must also be considered in the selection of the proper hose, e.g. fluid compatibility, temperatures, environment, etc.

For additional information on a specific hose, consult the respective hose listing in this catalog.

Parker Hose Number	Page Number	Hose Dash Size (I.D.)												
		-3	-4	-5	-6	-8	-10	-12	-16	-20	-24	-32	-40	-48
804	A-9		125		125	125		125						
801	A-9		250		250	250	250	250	175					
836	A-11		250		250	250	250							
821	A-10		350		300	300	250	250						
821FR	A-10		350		300	300		250						
831	A-11		350		300	300	300							
811 w/ HC Clamp	A-12							100	70	50	50	50	62	
811 w/ HC-H Clamp	A-12							300	250	200	150	10	62	
881 w/ HC Clamp	A-12							100	70	50	50	50	62	
881 w/ HC-H Clamp	A-12							300	250	200	150	10	62	
604	A-20				300	300			300					
SS25UL	A-3		350	350	350	350	350	350						
235	A-7								350					
285	A-8		400		400	400	400	400						
293	A-8		500		500	500	450	450	250					
221FR	A-6			500	500	500	500	500	500					
601	A-20		1250		1125	1000		750	565					
266	A-7		2000	1500	1500	1250	1250	750	400	300	250			
213	A-5		2000	1500	1500	1250	1000	750	400	300	300	200		
421	A-15	3000	2750	2500	2250	2000	1500	1250	1000	625	500	375		
421HT	A-15		2750		2250	2000	1500	1250	1000	625	500	375		
421WC	A-16		2750		2250	2000		1250	1000					
424	A-16								1000	625	500	375		
481	A-19		3250	3250	3000	2500	2000	1750	1275					
201/261	A-3		3000	3000	2250	2000	1750	1500	800	625	500	350	350	200
206	A-4		3000	3000	2250	2000	1750	1500	800	625	500	350	350	
225	A-6		3000	3000	2250	2000	1750	1500	800	625	500	350		
451TC	A-18		3000		3000	3000	3000	3000	3000					
304	A-14		5000		4000	3500		2250	2000	1625	1250	1125		
301	A-13		5000		4000	3500	2750	2250	2000	1625	1250	1125		
301LT	A-13		5000		4000	3500		2250	2000					
431	A-17		5000	4250	4000	3500	2750	2250	2000					
436	A-17				4000	3500	2750	2250	2000					
341	A-21				4500	4000		3000	3000	2500				
381	A-14		5500	5075	5000	4250	3625	3125	2500	2250	1800	1300		
471	A-18				5000	4250	3625	3125	2500					
471ST	A-19				5000	4250	3625	3125	2500					
701	A-21				6500	6000	5000	5000						
77C	A-23				4000	4000	4000	4000	4000	3000	2500	2500		
772	A-22				4000	4000	4000	4000	4000	3000	2500	2500		
774	A-23							4000	4000	3000	2500	2500		
782	A-24							5000	5000	5000	5000			
78C	A-24							5000	5000	5000	5000	5000		
731	A-22							6000	5500	4700	4200	3600		
792	A-25							6000	6000	6000				