

## 2.5 SERIES VALVING SPECIFICATIONS

### **COMPRESSION DAMPING**

VALVE OUTSIDE DIA.	#30	#35	#40	#45	#50	#55	#60	#65	#70	#75	#80	#85	#90	#95	#100	#105	#110	#115	#120
Ø 1.800"	0.008	0.008	0.008	0.008	0.010	0.010	0.010	0.012	0.012	0.012	0.012	0.015	2 X .010	2 X .012	2 X .015	3 X .015	4 X .015	4 X .015	
Ø 1.600"	0.008	0.008	0.008	0.01	0.010	0.010	0.010	0.012	0.012	0.012	0.012	0.015	2 X .010	2 X .012	2 X .015	2 X .015	2 X .015	3 X .015	
Ø 1.425"	0.008	0.008	0.010	0.010	0.010	0.010	0.012	0.012	0.012	0.012	0.015	0.015	0.015	0.015	0.015	0.015	0.015	0.015	
Ø 1.350"	0.008	0.010	0.010	0.010	0.010	0.012	0.012	0.012	0.012	0.015	0.015	0.015	0.015	0.015	0.015	0.015	0.015	0.015	
Ø 1.100"	0.008	0.010	0.010	0.010	0.010	0.012	0.012	0.012	0.012	0.015	0.015	0.015	0.015	0.015	0.015	0.015	0.015	0.015	
Ø .950"	0.008	0.010	0.010	0.010	0.010	0.012	0.012	0.012	0.012	0.015	0.015	0.015	0.015	0.015	0.015	0.015	0.015	0.015	
Ø .800"	0.020	0.020	0.020	0.020	0.020	0.020	0.020	0.020	0.020	0.020	0.020	0.020	0.020	0.020	0.020	0.020	0.020	0.020	
Ø1.57" TOP OUT	0.128	0.128	0.128	0.128	0.128	0.128	0.128	0.128	0.128	0.128	0.128	0.128	0.128	0.128	0.128	0.128	0.128	0.128	

### **REBOUND DAMPING**

VALVE OUTSIDE DIA.	#30	#35	#40	#45	#50	#55	#60	#65	#70	#75	#80	#85	#90	#95	#100	#105
Ø 1.600"	0.008	0.008	0.008	0.008	0.010	0.010	0.010	0.012	0.012	0.012	0.012	0.015	2 X .010	2 X .012	2 X .015	
Ø 1.425"	0.008	0.008	0.008	0.010	0.010	0.010	0.010	0.012	0.012	0.012	0.012	0.015	0.015	2 X .010	2 X .012	2 X .015
Ø 1.350"	0.008	0.008	0.010	0.010	0.010	0.010	0.012	0.012	0.012	0.012	0.015	0.015	0.015	0.015	0.015	0.015
Ø 1.100"	0.008	0.008	0.010	0.010	0.010	0.012	0.012	0.012	0.012	0.015	0.015	0.015	0.015	0.015	0.015	0.015
Ø .950"	0.008	0.010	0.010	0.010	0.010	0.012	0.012	0.012	0.012	0.015	0.015	0.015	0.015	0.015	0.015	0.015
Ø .800"	0.008	0.010	0.010	0.010	0.010	0.012	0.012	0.012	0.012	0.015	0.015	0.015	0.015	0.015	0.015	0.015
Ø .750" BACK UP	0.200	0.200	0.200	0.200	0.200	0.200	0.200	0.200	0.200	0.200	0.200	0.200	0.200	0.200	0.200	0.200

