

## Silverado Standard And Optional Features

With 1500, SS, 1500HD, 2500 and 3500 models to choose from, the Silverado family has a truck tailor made to your specifications. Ten engines, three cabs, three box sizes and several trim levels expand your choice further. And you can add to that from a series of packages and appealing options.

<b>S = Standard    O = Optional    - = Not Available</b>				
<b>Exterior</b>	<b>1500 Base</b>	<b>1500 LS</b>	<b>1500 LT</b>	<b>1500 SS</b>
Box extender (dealer installed accessory)	O	O	O	-
Box side rail protector (dealer installed accessory)	O	O	O	-
Box – Fleetside Short (5 ft. 8 in.) – 1500 Ext. and Crew Cab	S	S	S	-
Box – Fleetside Standard (6 ft. 6 in.) – 1500HD Crew Cab	-	S	S	S
Box – Fleetside Standard (6 ft. 6 in.) or Long (8 ft.) – 1500 Reg. and Ext. Cab	S	S	S	-
Bumpers – front, chrome with top cover (spectra gray on LS, painted on LT) and air dam, rear, chrome with step pad	S	S	-	-
Bumpers – front, integrated with colour-keyed fascia, rear, colour-keyed	-	-	S	S
Fender flares – wheel opening on 4x4s (standard on 1500HD models)	O	O	O	-
Fog lights	-	O	S	-
Glass – Solar-Ray tinted, all windows	S	S	S	S
Glass – deep-tinted on all windows behind front doors	O	O	S	S
Grille – chrome surround	O	S	-	-
Grille – colour-keyed	-	-	S	S
Mirrors – foldaway, black	S	S	S	-
Mirrors – power remote control, heated	-	S	-	-
Mirrors – power remote control, heated, power folding with reverse down, electrochromic auto-dimming driver's side and integral turn signals	-	O	S	S
Mirrors – deluxe wide-load, vertical glass with lower convex spotter glass, heated with integrated turn signals, manual extending and folding	-	O	O	-
Mirrors – camper-style, manual extending	O	-	-	-
Mouldings – bodyside, black	O	-	-	-
Mouldings – bodyside, colour-keyed	-	S	S	-
Package – 20" Chrome Wheel (LS, LT Extended Cab short and standard box models and LS, LT Crew Cab models, except Cheyenne) – 20" x 8.5" 5-spoke, chromed aluminum wheels; High-performance suspension (2WD models); P275/55R20 all-season performance tires; Rear axle ratio: 3.73:1	-	O	O	-
Package – 20" Chrome Wheel (Silverado Cheyenne models) – 20" x 8.5" 5-spoke, chromed aluminum wheels; P275/55R20 all-season performance tires	-	O	-	-
Package – Snow Plow Prep: includes wiring for roof-mounted light, heavy-duty front springs, high-capacity air cleaner and 160 amp alternator; requires available V8 engine; includes extra capacity transmission oil cooler (Reg. Cab 4x4 only)	O	O	-	-
Pickup box tonneau cover – soft or hard cover design (dealer installed accessory)	O	O	O	-
Recovery hooks – two front	S	S	S	S
Running boards – black, contoured (NA with Crew Cab) (dealer installed accessory)	O	O	O	-
Side steps – tubular design, chrome or black finish (dealer installed accessory)	O	O	O	-
Skid plates – off-road, standard with Z71 suspension (4x4 only)	O	O	O	-
Sunroof – power, with express-open and wind deflector (Ext. Cab standard and long box and Crew Cabs)	-	O	O	O
Tires – 17" wheels with size ranges from P245/70R17 up to P265/70R17 all-season (except SS, 1500HD and Hybrid models)	S	S	S	-
Tires – 16" wheels with LT245/75R16 all-season on 1500HD models	-	S	S	-
Tires – 16" wheels with P235/75R16 (2WD), P245/75R16 (4x4) on Hybrid models	-	S	S	-
Tires – 20" aluminum wheel package with 275/55R20 ALS (1500 Ext. Cab and Crew Cab models, standard on SS)	-	O	O	S
Wheels – 17" Styled steel. Painted silver (Value Leader Reg. Cab and Base Ext. Cab)	S	-	-	-
Wheels – 17" Chrome styled steel (Base Reg. Cab, LS models and Crew Cab Cheyenne model)	S	S	-	-
Wheels – 16" Cast aluminum (Hybrid model)	-	S	S	-
Wheels – 17" Polished cast aluminum (Crew Cabs and Ext. Cab LT models)	-	S	S	-
Wheels – 20" Chromed aluminum (LS/LT Ext. and Crew Cabs, except Cheyenne)	-	O	O	-
Wheels – 20" Sport aluminum	-	-	-	S

<b>Interior</b>	<b>1500 Base</b>	<b>1500 LS</b>	<b>1500 LT</b>	<b>1500 SS</b>
Air conditioning – dual-zone, manual climate control (excludes Reg. Cab)	S	S	S	–
Air conditioning – dual-zone, automatic climate control	–	O	S	O
Console – mini overhead	–	S	S	S
Cruise control – electronic with resume, coast and decelerate/accelerate features	O	S	S	S
Cupholders – dual	S	S	S	S
Defogger – electric, rear-window (except Cheyenne)	O	S	S	S
Floor covering – colour-keyed carpet and removable vinyl floor mats (includes rear in Ext. and Crew Cabs)	O	S	S	S
Instrumentation – analogue, including speedometer, tachometer, voltmeter, coolant temperature, oil pressure, fuel gauge, odometer, trip odometer and engine hour meter	S	S	S	S
Instrumentation – Driver Information Centre, comprehensive multi-language system that displays numerous vehicle functions with both visual and audible reminders/warnings	S	S	S	S
Mirror – rear-view, electrochromic auto-dimming with compass and exterior temperature readouts (except Cheyenne)	–	S	S	S
Personalization features – programs many comfort and convenience features using the steering wheel controls, including automatic locking/unlocking, seat position recall, perimeter lighting, exit lighting, remote lock/unlock feedback and reverse down of exterior mirrors	–	–	S	–
Power outlet – one auxiliary, 12-volt, in addition to cigarette lighter receptacle	S	S	S	S
Smoker's Package – includes lighter and ashtray (standard with bench seating)	S	O	O	O
Steering column – tilt adjustable	S	S	S	S
Steering wheel – leather-wrapped, (except Cheyenne)	–	S	S	S
Stowage box – under rear seat (Ext. Cab standard and long box only)	O	O	O	S
Sunshades – LH and RH padded colour-keyed cloth with extenders; LH with pocket, RH with visor mirror	S	S	S	S
Windows – power, driver's side express-down and passenger lock-out feature	–	S	S	S
Window – rear, manual sliding	O	O	O	–

<b>Mechanical</b>	<b>1500 Base</b>	<b>1500 LS</b>	<b>1500 LT</b>	<b>1500 SS</b>
Brakes – power, front disc/rear drum with 4-wheel anti-lock braking system (ABS)	S	S	S	S
Brakes – power, 4-wheel disc with 4-wheel anti-lock braking system (ABS) on 1500HD and Hybrid models	–	S	S	–
Engine – Vortec 4.3L V6 (Reg. Cab and 2WD Ext. Cab Standard box)	S	S	–	–
Engine – Vortec 4.8L V8 (Reg. and Ext. Cabs except Reg. Cab and 2WD Ext. Cab with Standard box)	O	S	–	–
Engine – Vortec 5.3L V8 (Reg. and Ext. Cabs)	O	O	S	–
Engine – Vortec 5.3L V8 (Crew Cabs)	–	O	O	–
Engine – VortecMAX 6.0L V8	–	O	O	S
Engine – block heater	S	S	S	S
Exhaust system – aluminized stainless steel muffler and tailpipe	S	S	S	S
Locking differential – rear (standard on SS and all 4x4 models except Cheyenne)	O	O	O	S
Package – Silverado Cheyenne (LS Crew Cab 1500 2WD and 4x4 models) – 285 hp Vortec 4.8L V8; 4-speed automatic transmission; Heavy-duty suspension; Tires: P245/70R17 all-season on 2WD models, P265/70R17 all-season on 4x4 models; Dual-zone manual climate control air conditioning; AM/FM stereo with CD player	–	O	–	–
Package – Silverado Special Edition (Base Regular or Extended Cab 1500 2WD and 4x4 models) – Custom cloth seat trim; Heavy-duty suspension (standard on 4x4s); 17" aluminum wheels; Deep-tinted glass on all windows behind front doors; Locking rear differential (standard on 4x4s); Chromed stainless steel tubular side steps; Silverado Special Edition decals	O	–	–	–
Package – Silverado Special Edition (LS Regular, Extended and Crew Cab 1500 2WD and 4x4 models) – Heavy-duty suspension (standard on 4x4 and Crew Cab models); 17" aluminum wheels; Deep-tinted glass on all windows behind front doors; Fog lights; Locking rear differential (standard on 4x4s); Chromed stainless steel tubular side steps; Silverado Special Edition decals	–	O	–	–
Package – Silverado Performance Edition (LS, LT Extended Cab 1500 with standard box, 2WD models) – 345 hp VortecMAX 6.0L V8 engine; 4-speed Heavy-duty automatic transmission (4L65E); Auxiliary transmission oil cooler; High-performance suspension; 20" x 8.5" 5-spoke, chromed-finish aluminum wheels; P275/55R20 all-season performance tires; VortecMAX door badge and engine cover decal	–	O	O	–
Package – Value Leader Regular Cab – Engine: 195 hp Vortec 4.3L V6; Transmission: 5-speed manual with overdrive; Suspension: Standard (Z83) with 2WD/Heavy-Duty (Z85) with 4x4; Grille: gray surround; Wheels: 17" styled steel wheels with centre cap, painted silver; Seats: 40/20/40 split-bench, vinyl or cloth trim; Floor covering: black vinyl	O	–	–	–
Package – Vortec 5.3L V8 Hauler (LS Regular and LS, LT Extended Cab 2WD models with Fleetside standard or long box) – 295 hp Vortec 5.3L V8 (standard on SLE Extended Cab long box and SLT models; Extended Cab 4x4 standard box models feature the aluminum block High-Output Vortec 5.3L V8 with 310 hp); Trailering Special Equipment Package; Locking rear differential; ZX3 Adjustable Ride Control suspension	–	O	O	–
Package – Vortec 5.3L V8 Hauler (LS, LT Crew Cab 2WD models with Fleetside short box) – Trailering Special Equipment Package; Locking rear differential	–	O	O	–
Package – Vortec 5.3L V8 Off-Road (LS Regular and LS, LT Extended Cab 4x4 models with Fleetside standard or long box) – 295 hp Vortec 5.3L V8 (standard on LS Extended Cab long box and LT models; Extended Cab 4x4 standard box models feature the aluminum block High-Output Vortec 5.3L V8 with 310 hp); Trailering Special Equipment Package; Z71 Off-Road Suspension Package; P265/70R17 On/Off Road tires; Autotrac 4x4 transfer case (standard on LT and up-level LS Extended Cab models)	–	O	O	–
Package – Vortec 5.3L V8 Off-Road (LS, LT Crew Cab 4x4 models with Fleetside short box) – Trailering Special Equipment Package; Z71 Off-Road Suspension Package	–	O	O	–
Package – VortecMAX Performance (LS, LT Extended Cab standard box and Crew Cab 1500 2WD and 4x4 models) – Heavy-duty rear axle with a 9.5 in. diameter ring gear; Engine oil cooler; P265/70R17 On/Off Road tires; 345 hp VortecMAX 6.0L V8 engine; 4-speed super-duty automatic transmission (4L70E); Adjustable Ride Control Suspension; Autotrac transfer case (standard on Crew Cab and 4x4 models); Trailering Special Equipment Package; VortecMAX door badge and engine cover decal	–	O	O	–
Steering – power, rack-and-pinion on 1500 series 2WD models	S	S	S	S
Steering – power, recirculating ball on all other models	S	S	S	–
Suspension – Z83 Standard (2WD models)	S	S	–	–
Suspension – Z85 Heavy-duty (4x4 models and 2WD LT Ext. Cabs)	S	S	S	–

Suspension – ZX3 Ride Control (4x4 models and LS/LT 2WD models)	O	O	O	–
Suspension – Z71 Off-Road (4x4 models)	–	O	O	–
Suspension – Z60 High Performance	–	–	–	S
Trailer Special Equipment Package – heavy-duty, includes weight-distributing platform trailer hitch receiver, 8-lead wiring harness with a 7-pin sealed connector (includes trailer brake control harness), heavy-duty transmission oil cooler and high-capacity air cleaner	O	O	O	O
Transfer case (4x4 models) – lever-operated 2-speed manual	S	S	–	–
Transfer case (4x4 models) – Autotrac with electronic push-button controls (standard on Hybrid and LS Crew Cab except Cheyenne)	–	O	S	–
Transmission – 5-speed manual with overdrive (Base Reg. Cab with Vortec 4.3L V6 only)	S	–	–	–
Transmission – 4-speed automatic with overdrive and Tow/Haul mode (optional on Base Reg. Cab)	S	S	S	–
Transmission – Heavy-duty 4-speed automatic with overdrive and Tow/Haul mode	–	–	–	S

<b>Safety &amp; Security</b>	<b>1500 Base</b>	<b>1500 LS</b>	<b>1500 LT</b>	<b>1500 SS</b>
Air bags – dual-stage, driver and front passenger-side, frontal. Includes Passenger Sensing System with automatic air bag suppression (1500 models only)	S	S	S	S
Air bags – single-stage, driver and front-passenger, frontal (1500HD models only)	–	S	S	S
Brake/transmission shift interlock (automatic transmission only)	S	S	S	S
Door locks – power, programmable with lock-out protection	O	S	S	S
Headlights – with automatic light control	S	S	S	S
Keyless entry system – remote, programmable with Panic alarm feature	–	S	S	S
OnStar® In-Vehicle Communications and Assistance Service – includes one-year Safe & Sound Plan	–	O	S	O
Safety restraints – LATCH (Lower Anchors and top Tethers for Children) – Ext. and Crew Cab only	S	S	S	S
Theft-deterrent system – PASSLock	S	S	S	S
Traction assist – electronic, 2WD models	O	O	O	S

<b>Seats</b>	<b>1500 Base</b>	<b>1500 LS</b>	<b>1500 LT</b>	<b>1500 SS</b>
Front, 40/20/40 split-bench with manual driver's side recliner – vinyl or cloth trim	S	–	–	–
Front, Custom cloth, 40/20/40 split-bench with manual recliners and centre armrest/storage – Ext. and Crew Cab also include seatback storage pockets	O	S	–	S
Front, 40/20/40 split-bench with leather seat inserts and driver's side power 6-way seat adjuster; rear seats are vinyl on LS and LT Extended Cab models when leather seat inserts are specified (NA on Reg. Cab)	–	O	–	O
Front bucket seats with manual recliners, power 6-way driver seat adjuster, driver and front-passenger inboard armrests – includes seatback storage pockets and centre floor console – Custom cloth or leather seat inserts; rear seats are vinyl on LS and LT Extended Cab models when leather seat inserts are specified (except Reg. Cab)	–	O	–	–
Full-feature front bucket seats with heated leather seat inserts, driver's side two-position memory controls and power 10-way driver and front passenger seat adjusters including power lumbar supports and seatback recliners. Includes driver and front passenger-side inboard armrests, seatback storage pockets and floor console	–	–	S	O
Leather front seat inserts – Ext. and Crew Cab	–	O	S	O
Head restraints, adjustable on all outboard seats	S	S	S	S
Power 6-way driver seat adjuster on 40/20/40 split-bench seat	–	O	–	O
Rear, fold-up seat on Ext. Cab (rear seats are vinyl on LS and LT Extended Cab models when leather seat inserts are specified)	S	S	S	S
Rear, 60/40 split fold-down seat on Crew Cab	–	S	S	–

<b>Entertainment</b>	<b>1500 Base</b>	<b>1500 LS</b>	<b>1500 LT</b>	<b>1500 SS</b>
AM/FM stereo with seek/scan, digital clock and 4 speakers	S	–	–	–
AM/FM stereo with seek/scan, CD player, Radio Data System (RDS), auto tone control, digital clock and 6 speakers (4 speakers on Reg. Cab)	O	S	–	S
AM/FM stereo with seek/scan, cassette tape, CD player, Radio Data System (RDS), auto tone control, digital clock and 6 speakers (4 speakers on Reg. Cab)	–	O	O	O
AM/FM stereo with seek/scan, 6-disc CD changer, Radio Data System (RDS), auto tone control, digital clock and 6 Bose premium speakers	–	O	S	O
XM Satellite Radio (includes three trial months beyond which service fees apply; available in 10 Canadian provinces and 48 contiguous United States)	–	O	O	O
Bose premium speakers, included with bucket seats	–	O	S	O
Steering wheel audio controls	–	O	S	O
Rear-seat audio controls (Crew Cab)	–	O	S	–
DVD Entertainment Package – includes rear-seat overhead fold-down 178 mm (7 in.) LCD colour monitor, DVD player, video game input (RCA) jacks, rear-seat audio controls and 2 wireless headphones (Crew Cab with bucket seats)	–	O	O	–
Family Cab Package (LS, LT Crew Cab 1500 models) – Entertainment Package includes DVD player and wireless headphones; XM Satellite Radio*; Power sunroof (*includes 3 trial months beyond which service fees apply; available in 10 Canadian Provinces and 48 contiguous United States)	–	O	O	–

## SPECIFICATIONS - SILVERADO 1500

Engines	Vortec 4300 4.3L V-6 (LU3)	Vortec 4800 4.8L V-8 (LR4)	Vortec 5300 5.3L V-8 (LM7) including Hybrid model	Vortec 5300 5.3L V-8 (L33)
Type:	4.3L V-6	4.8L V-8	5.3L V-8	5.3L V-8
Displacement (cc / cu in):	4300 / 262	4807 / 293	5328 / 325	5328 / 325
Bore & stroke (mm / in):	101.6 x 88 / 4 x 3.48	96.01 x 83 / 3.78 x 3.27	96.01 x 92 / 3.78 x 3.62	96.01 x 92 / 3.78 x 3.62
Block material:	Cast iron	Cast iron	Cast iron	Aluminum with iron cylinder sleeves
Cylinder head material:	Cast iron	Cast aluminum	Cast aluminum	Cast aluminum
Valvetrain:	OHV, 2 valves per cylinder	OHV, 2 valves per cylinder	OHV, 2 valves per cylinder	OHV, 2 valves per cylinder
Ignition system:	Direct composite distributor, long-life spark plugs, low-resistance spark plug wires	Coil near plug, iridium-tipped spark plugs, low-resistance spark plug wires	Coil near plug, ignition, iridium-tipped spark plugs, low-resistance spark plug wires	Coil near plug, composite distributor, iridium-tipped spark plugs, low-resistance spark plug wires
Fuel delivery:	Sequential fuel injection	Sequential fuel injection	Sequential fuel injection	Sequential fuel injection
Compression ratio:	9.2:1	9.5:1	9.5:1	9.9:1
Horsepower (hp / kw @ rpm):	195 / 145 @ 4600	285 / 201 @ 5200	295 / 220 @ 5200	310 / 231 @ 5200
Torque (lb.-ft. / Nm @ rpm):	260 / 353 @ 2800	295 / 398 @ 4000	335 / 463 @ 4000	335 / 463 @ 4000
Recommended fuel:	87 octane	87 octane	87 octane	87 octane
Maximum engine speed (rpm):	manual: 5600 automatic: 5600	manual: 5600 automatic: 6000	manual: 5600 automatic: 6000	manual: 5600 automatic: 6000
Emissions controls:	3-way catalytic converter, exhaust gas recirculation, positive crankcase ventilation, evaporative collection system			

Engines (cont'd)	Vortec 5300 5.3L V-8 (L59)	Vortec 6000 6.0L V-8 (LQ4) (Silverado SS & VortecMAX Performance Package)	
	Flexible Fuel	6.0L V-8	6.0L V-8
Type:	5.3L V-8	6.0L V-8	6.0L V-8
Displacement (cc / cu in):	5328 / 325	5967 / 364	5967 / 364
Bore & stroke (mm / in):	96 x 92 / 3.78 x 3.62	101.6 x 92 / 4 x 3.62	101.6 x 92 / 4 x 3.62
Block material:	Cast iron	Cast iron	Cast iron
Cylinder head material:	Cast aluminum	Cast aluminum	Cast aluminum
Valvetrain:	OHV, 2 valves per cylinder	OHV, 2 valves per cylinder	OHV, 2 valves per cylinder
Ignition system:	Coil near plug ignition, iridium-tipped spark plugs, low-resistance spark plug wires	Coil near plug ignition, iridium-tipped spark plugs, low-resistance spark plug wires	Coil near plug, iridium-tipped spark plugs, low-resistance spark plug wires
Fuel delivery:	Sequential fuel injection	Sequential fuel injection	Sequential fuel injection
Compression ratio:	9.5:1	9.4:1	10:01
Horsepower (hp / kw @ rpm):	295 / 220 @ 5200	300 / 224 @ 4400	345 / 257 @ 5200
Torque (lb.-ft. / Nm @ rpm):	335 / 463 @ 4000	360 / 488 @ 4000	380 / 515 @ 4000
Recommended fuel:	87 octane or E85 (Ethanol)	87 octane	87 octane (premium recommended but not required)
Maximum engine speed (rpm):	manual: 5600 automatic: 6000	manual: 5600 automatic: 5600	manual: 5600 automatic: 5600
Emissions controls:	3-way catalytic converter, exhaust gas recirculation, positive crankcase ventilation, evaporative collection system		

#### Estimated fuel economy:

	Silverado - Classic (2WD)	Silverado - Classic (4WD)
	4.3L	4.3L
Mi / imp.gal (city / hwy / combined)	auto: 20 / 28 / 23 man: 20 / 30 / 23	auto: 19 / 25 / 21 man: 18 / 26 / 21
L/100km (city / hwy / combined)	auto: 13.9 / 10.1 / 12.2 man: 14.4 / 9.5 / 12.2	auto: 15.0 / 11.4 / 13.4 man: 15.4 / 10.7 / 13.3
	4.8L	4.8L
Mi / imp.gal (city / hwy / combined)	auto: 20 / 27 / 23	auto: 18 / 25 / 21
L/100km (city / hwy / combined)	auto: 14.3 / 10.3 / 12.5	auto: 15.4 / 11.5 / 13.7
	5.3L	5.3L
Mi / imp.gal (city / hwy / combined)	auto: 19 / 27 / 22 auto: 21 / 27 / 24 (hybrid) auto: 19 / 27 / 22 (flexible fuel-gasoline) auto: 14 / 21 / 17 (flexible fuel-ethanol)	auto: 18 / 25 / 20 auto: 20 / 25 / 22 (hybrid) auto: 18 / 24 / 20 (flexible fuel-gasoline) auto: 13 / 18 / 15 (flexible fuel-ethanol)
L/100km (city / hwy / combined)	auto: 14.6 / 10.4 / 12.7 auto: 13.2 / 10.4 / 12.0 (hybrid) auto: 15.1 / 10.4 / 13.0 (flexible fuel-gasoline) auto: 19.9 / 13.7 / 17.1 (flexible fuel-ethanol)	auto: 15.9 / 11.3 / 13.9 auto: 14.3 / 11.3 / 13.0 (hybrid) auto: 15.9 / 11.7 / 14.0 (flexible fuel-gasoline) auto: 21.0 / 15.5 / 18.6 (flexible fuel-ethanol)
	6.0L	6.0L
Mi / imp.gal (city / hwy / combined)	auto: 17 / 24 / 20	auto: 17 / 22 / 19
L/100km (city / hwy / combined)	auto: 16.2 / 11.7 / 14.2	auto: 17.0 / 12.8 / 15.1

**Estimated fuel economy:**

	<b>Silverado - New (2WD)</b>	<b>Silverado - New (4WD)</b>
	<b>4.3L</b>	<b>4.3L</b>
Mi / imp.gal (city / hwy / combined)	auto: 20 / 28 / 23	auto: 19 / 25 / 21
L/100km (city / hwy / combined)	auto: 14.1 / 10.2 / 12.4	auto: 15.0 / 11.3 / 13.3
	<b>4.8L</b>	<b>4.8L</b>
Mi / imp.gal (city / hwy / combined)	auto: 19 / 27 / 22	auto: 18 / 25 / 20
L/100km (city / hwy / combined)	auto: 14.8 / 10.6 / 12.9	auto: 15.7 / 11.5 / 13.8
	<b>5.3L</b>	<b>5.3L</b>
	auto: 20 / 29 / 23	auto: 19 / 27 / 22
Mi / imp.gal (city / hwy / combined)	auto: 20 / 28 / 23 (flexible fuel-gasoline) auto: 15 / 21 / 17 (flexible fuel-ethanol)	auto: 19 / 26 / 22 (flexible fuel-gasoline) auto: 14 / 19 / 16 (flexible fuel-ethanol)
L/100km (city / hwy / combined)	auto: 14.3 / 9.9 / 12.3 auto: 14.3 / 10.0 / 12.3 (flexible fuel-gasoline) auto: 19.3 / 13.4 / 16.6 (flexible fuel-ethanol)	auto: 15.0 / 10.6 / 13.0 auto: 15.1 / 10.8 / 13.1 (flexible fuel-gasoline) auto: 20.3 / 14.5 / 17.7 (flexible fuel-ethanol)
	<b>6.0L</b>	<b>6.0L</b>
Mi / imp.gal (city / hwy / combined)	auto: 18 / 25 / 21	auto: 17 / 24 / 20
L/100km (city / hwy / combined)	auto: 15.7 / 11.2 / 13.7	auto: 16.3 / 11.7 / 14.2

<b>Transmissions</b>	<b>NV3500 (MG5)</b>	<b>NV4500 (MW3)</b>	<b>Hydra-Matic 4L60-E (M30/M33)</b>	<b>Hydra-Matic 4L80-E</b>	<b>Hydra-Matic 4L85</b>	<b>Hydra-Matic 4L85-E (Silverado SS)</b>
Type:	5-speed manual	5-speed manual	4-speed automatic	4-speed automatic	4-speed automatic	4-speed automatic
<b>Gear ratios (:1):</b>						
First:	4.02	5.61	3.06	2.48	2.48	3.06
Second:	2.32	3.04	1.63	1.48	1.48	1.63
Third:	1.4	1.67	1.00	1.00	1.00	1.00
Fourth:	1.00	1.00	0.70	0.75	0.75	0.70
Fifth:	0.73	0.75	-	-	-	-
Reverse:	3.55	5.04	2.29	2.07	2.07	2.29
Final drive ratio:	3.08 3.42 3.73 4.10	3.42 3.73 4.10	3.08 3.42 3.73 4.10	3.42 3.73 4.10	4.1	



## Chassis/Suspension

Front:	1500 4WD: independent with computer-selected torsion bars, 28.6-mm stabilizer bar 1500 2WD: computer-selected coil springs; gas-pressurized shocks; 31.8-mm stabilizer bar
Rear:	Solid axle with semi-elliptic, variable-rate, two-stage multileaf springs; gas-pressurized shocks
Traction control:	2WD only
Steering type	
4WD	Power recirculating ball
2WD	Power rack-and-pinion
Steering ratio:	14.2:1
Steering wheel turns, lock-to-lock:	3
Turning circle, curb-to-curb (m / ft):	
2WD Reg. Cab Standard Box:	12.2 / 40.1
2WD Ext. Cab Standard Box:	14.2 / 46.6
4WD Ext. Cab Standard Box:	14.4 / 47.3
2WD 1500 Crew Cab Short Box:	14.2 / 46.6
4WD 1500 Crew Cab Short Box:	14.4 / 47.3

## Brakes

Type:	Vacuum booster, power, 4-wheel disc, 4-wheel ABS, DRP; or vacuum booster, power, front disc/rear drum, 4-wheel ABS, DRP
<b>Rotor diameter x thickness (mm / in)</b>	
1500 with disc/drum brakes:	front: 330 x 30 / 12.99 x 1.18 rear: 295 x 60 / 11.61 x 2.36
1500 with 4-wheel disc:	front: 302 x 30 / 11.88 x 1.18 rear: 325 x 20 / 12.8 x 0.78
1500HD, 2500:	front: 325 x 38 / 12.8 x 1.5 rear: 330 x 29 / 13 x 1.14
<b>Total swept area (sq in / sq cm)</b>	
1500 with disc/drum brakes:	front: 1944 / 301.2 rear: 1112 / 172.4
1500 with 4-wheel disc:	front: 1378 / 213.6 rear: 1362 / 211.1
1500HD, 2500:	front: 1584 / 245.5 rear: 1526 / 236.5

## Wheels/Tires

### Wheel size & type:

Work Truck	6-lug 17-inch x 7.0-inch painted steel (std)
2WD Reg and Ext cab, 2WD/4WD Crew Cab:	6-lug 17-inch x 7.5-inch chrome-style steel (std w/YE9, opt w/o YE9) 6-lug 17-inch x 7-inch cast alum (opt on all) 6-lug 20-inch x 8.5-inch chrome alum (std w/B4V) 6-lug 20-inch x 8.5-inch chrome alum (std w/Silverado SS)
1500HD:	8-lug 16-inch x 6.5-inch chrome-style steel (std) 8-lug 16-inch x 6.5-inch cast alum (opt)

### Tires:

2WD:	P245/70R17-108S all-season blackwall (std) P245/70R17-108S all-season white-outlined letter (opt) P275/55R20-111S touring blackwall (std w/B4V) P235/75R16-106S all-season blackwall (std w/PHT) P235/75R16-106S all-season white-outlined letter (opt w/PHT)
4WD (Reg/Ext. Cab):	P265/70R17-113S all-season blackwall (std) P265/70R17-113S all-season, white outlined-letter (opt) P265/70R17-113S on-off road blackwall (opt) P265/70R17-113S on-off road white outlined letter (opt) P245/55R20-111S touring blackwall (std w/Silverado SS) P245/75R20-109S all season blackwall (std w/PHT) P245/75R20-109S all season white outlined letter (opt w/PHT)
4WD Crew Cab:	P265/70R17-113S all-season blackwall (std) P265/70R17-113S all-season white-outlined letter (opt)
1500HD 2WD/4WD:	LT245/75R16E-120S all season blackwall (opt) LT245/75R16E-120S on-off road blackwall (opt) P245/75R16-109S all-season white outlined letter (opt) P265/75R16-109S all-terrain, blackwall (opt) P265/75R16-109S all-terrain, white outlined letter (opt) LT245/75R16C-108R on-off road blackwall (opt) LT245/75R16C-108R on-off road white outlined letter (opt)

Exterior Dimensions	Regular Cab, Standard Box	Regular Cab, Long Box	Extended Cab, Standard Box	Extended Cab, Long Box
	CC15703, CK15703	CC15903, CK15903	CC15753, CK15753	CC15953, CK15953
Wheelbase (mm / in):	3023 / 119	3378 / 133	3645 / 143.5	4000 / 157.5
Overall length (mm / in):	5154 / 202.9	5636 / 221.9	5776 / 227.4	6264 / 246.6
Overall width (mm / in)	Base/fleet: 1994 / 78.5	Base/fleet: 1994 / 78.5	Base/fleet: 1994 / 78.5	Base/fleet: 1994 / 78.5
	With YE9 package opt mirrors folded 2070 / 81.5	With YE9 package opt mirrors folded 2070 / 81.5	With YE9 package opt mirrors folded 2070 / 81.5	With YE9 package opt mirrors folded 2070 / 81.5
	With YE9 package opt mirrors extended: 236 / 93.13	With YE9 package opt mirrors extended: 2363 / 93.1	With YE9 package opt mirrors extended: 2363 / 93.1	With YE9 package opt mirrors extended: 2363 / 93.1
Overall height (mm / in)	2WD: 1808 / 71.2 4WD: 1875 / 73.8	2WD: 1803 / 71.0 4WD: 1872 / 73.7	2WD: 1808 / 71.2 4WD: 1877 / 73.9	2WD: 1798 / 70.8 4WD: 1872 / 73.7
Track (mm / in)	front: 1651 / 65 rear: 1676 / 66	front: 1651 / 65 rear: 1676 / 66	front: 1651 / 65 rear: 1676 / 66	front: 1651 / 65 rear: 1676 / 66
Min. ground clearance (mm / in):	2WD: 269 / 10.6 4WD: 213 / 8.4	2WD: 231 / 9.1 4WD: 213 / 8.4	2WD: 203 / 8 4WD: 221 / 8.7	2WD: 203 / 8 4WD: 213 / 8.4
Ground to top of load floor (mm / in):	2WD: 803 / 31.6 4WD: 856 / 33.7	2WD: 803 / 31.6 4WD: 856 / 33.7	2WD: 803 / 31.6 4WD: 856 / 33.7	2WD: 803 / 31.6 4WD: 856 / 33.7
Step-in height (mm / in):	2WD: 495 / 19.5 4WD: 540 / 21.3	2WD: 495 / 19.5 4WD: 540 / 21.3	2WD: 495 / 19.5 4WD: 540 / 21.3	2WD: 495 / 19.5 4WD: 540 / 21.3
Approach angle (deg.):	28	28	28	28
Breakover angle (deg.):	14	14	14	14
Departure angle (deg.):	23	23	23	23

Exterior (cont'd)	Extended Cab, Short Box	Crew Cab, Short Box	Crew Cab, Standard Box
	CC15553, CK15553	CC15543, CK15543	(1500HD) CC15743, CK15743
Wheelbase (mm / in):	3404 / 134	3645 / 143.5	3886 / 153
Overall length (mm / in):	5535 / 217.9	5779 / 227.5	6025 / 237.2
Overall width (mm / in)	Base/fleet: 1994 / 78.5	Base/fleet: 1994 / 78.5	Base/fleet: 2024 / 79.7
	With YE9 package opt mirrors folded 2070 / 81.5	With YE9 package opt mirrors folded -	With YE9 package opt mirrors folded 2070 / 81.5
	With YE9 package opt mirrors extended: 2363 / 93.1	With YE9 package opt mirrors extended: -	With YE9 package opt mirrors extended: 2363 / 93.1
Overall height (mm / in)	2WD:71.2 / 1808 4WD:73.9 / 1877	2WD:72.6 / 1844 4WD:1905 / 75.0	2WD:1956 / 77.0 4WD:1963 / 77.3
	Track (mm / in) front: 1651 / 65 rear: 1676 / 66	front: 1651 / 65 rear: 1676 / 66	front: 1899 / 68.6 rear: 1676 / 66
Min. ground clearance (mm / in):	2WD: 203 / 8 4WD: 221 / 8.7	2WD: 206 / 8.1 4WD: 220 / 8.7	2WD: 231 / 9.1 4WD: 269 / 8.3
	Ground to top of load floor (mm / in):	2WD: 803 / 31.6 4WD: 856 / 33.7	2WD: 803 / 31.6 4WD: 856 / 33.7
Step-in height (mm / in):	2WD: 495 / 19.5 4WD: 540 / 21.3	2WD: 495 / 19.5 4WD: 540 / 21.3	2WD: 495 / 19.5 4WD: 637.5 / 25.1
	Approach angle (deg.):	28	28
Breakover angle (deg.):	14	14	14
Departure angle (deg.):	23	23	23

	GVWR (kg / lb)	Curb Weight (kg / lb)	Payload (kg / lb)	Weight Distribution (% front / rear)
<b>2WD Pickups:*</b>				
C15703 Reg. Cab Stand. Box:	2767 / 6100	1910 / 4211	857 / 1889	57 / 43
C15903 Reg. Cab Long Box:	2903 / 6400	1972 / 4348	931 / 2052	57.9 / 42.1
C15753 Ext. Cab Stand. Box:	2948 / 6500	2098 / 4625	851 / 1875	57.9 / 42.1 (w/ LM7)
C15953 Ext. Cab Long Box:	3039 / 6700	2220 / 4894	819 / 1806	59 / 41 (w/ LM7)
C15553 Ext. Cab Short box:	2812 / 6200	2159 / 4760	653 / 1440	41 / 59
C15543 Crew Cab Short Box:	3130 / 6900	2262 / 4987	868 / 1913	57.6 / 42.4
C15743 1500HD Crew Cab Short Box:	3901 / 8600	2482 / 5471	1419 / 3129	57.6 / 42.4
<b>4WD Pickups:*</b>				
K15703 Reg. Cab Stand. Box:	2903 / 6400	2045 / 4508	858 / 1892	58 / 42
K15903 Reg. Cab Long Box:	2903 / 6400	2102 / 4634	801 / 1766	58.8 / 41.2
K15753 Ext. Cab Stand. Box:	3039 / 6700	2290 / 5050	748 / 1650	59.9 / 40.1 (w/ LM7)
K15953 Ext. Cab Long Box:	3039 / 6700	2375 / 5232	666 / 1468	59.8 / 40.2 (w/ LM7)
K15553 Ext. Cab Short Box:	2903 / 6400	2290 / 5050	612 / 1350	58.4 / 41.6
K15543 Crew Cab Short Box:	3175 / 7000	2397 / 5284	778 / 1716	60 / 40
K15743 1500HD Crew Cab Short Box:	3901 / 8600	2614 / 5762	1287 / 2838	59.2 / 40.8

<b>Cargo Box</b>	<b>Std. Box Fleetside</b>	<b>Long Box Fleetside</b>	<b>Short Box</b>
Cargo volume (L / cu ft):	1611 / 56.9	2092.8 / 73.9	1405 / 49.6
Length at floor (mm / in):	1999 / 78.7	2479 / 97.6	1758 / 69.2
Width at floor (mm / in):	1646 / 64.8	1646 / 64.8	1529 / 60.2
Width at top (mm / in):	1572 / 61.9	1572 / 61.9	1572 / 61.9
Width between wheelhousings (mm / in):	1270 / 50	1270 / 50	1270 / 50
Tailgate width (mm / in):	1621 / 63.8	1621 / 63.8	1539 / 60.6
Inside height (mm / in):	495 / 19.5	495 / 19.5	495 / 19.5

<b>Interior Dimensions</b>	<b>Regular Cab</b>	<b>Extended Cab, front</b>	<b>Extended Cab, rear</b>
Head room (mm / in):	1041 / 41	1041 / 41	975 / 38.4
Legroom (mm / in):	1049 / 41.3	1049 / 41.3	856 / 33.7
Shoulder room (mm / in):	1560 / 61.4	1560 / 61.4	1654 / 65.1
Hip room (mm / in):	1623 / 63.9	1623 / 63.9	1560 / 61.4

<b>Interior (cont'd)</b>	<b>1500 Crew Cab, front</b>	<b>1500 Crew Cab, rear</b>	<b>2500 Crew Cab, front</b>	<b>2500 Crew Cab, rear</b>
Head room (mm / in):	1034 / 40.7	1021 / 40.2	1044 / 41.1	1013 / 39.9
Legroom (mm / in):	1049 / 41.3	993 / 39.1	1049 / 41.3	990 / 38.8
Shoulder room (mm / in):	1560 / 61.4	1654 / 65.1	1560 / 61.4	1654 / 65.1
Hip room (mm / in):	1623 / 63.9	1560 / 61.4	1623 / 63.9	1560 / 61.4

Capacities	Regular Cab, Standard Box	Regular Cab, Long Box	Extended Cab, Standard Box	Extended Cab, Long Box	Extended Cab, Short Box
	CC15703, CK15703	CC15903, CK15903	CC15753, CK15753	CC15953, CK15953	CC15553, CK15553
Seating:	2 / 3	2 / 3	5 / 6	5 / 6	5 / 6
Fuel tank (L / imp.gal):	98.4 / 26	128.7 / 34	98.4 / 26	128.7 / 34	98.4 / 26

Capacities (cont'd)	Crew Cab, Short Box	Crew Cab, Standard Box (1500HD)
	CC15543, CK15543	CC15743, CK15743
Seating:	5 / 6	5 / 6
Fuel tank (L / imp.gal):	98.4 / 26	98.4 / 26

**Trailer towing  
maximum (kg /  
lb):**

Reg. Cab, Std. Box	2WD: 3810 / 8400; with 5.3L V-8, auto. Trans., 3.73 axle (req. weight distributing hitch) 4WD: 4128 / 9100; with 5.3L V-8, auto. Trans., 4.10 axle (req. weight distributing hitch)
Reg. Cab, Long Box	2WD: 3719 / 8200; with 5.3L V-8, auto. Trans., 3.73 axle (req. weight distributing hitch) 4WD: 4037 / 8900; with 5.3L V-8, auto. Trans., 4.10 axle (req. weight distributing hitch)
Ext. Cab, Std. Box	2WD: 3538 / 7800; with 6.0L V-8, auto. Trans., 3.73 axle (req. weight distributing hitch) 4WD: 3946 / 8700; with 5.3L V-8, auto. Trans., 4.10 axle (req. weight distributing hitch)
Ext. Cab, Std. Box (w/ VortecMAX)	2WD: 4717 / 10400; with 6.0L V-8, auto. trans., 4.10 axle (req. weight distributing hitch) 4WD: 4581 / 10100; with 6.0L V-8, auto. trans., 4.10 axle (req. weight distributing hitch)
Ext. Cab., Long Box	2WD: 3538 / 7800; with 5.3L V-8, auto. Trans., 3.73 axle (req. weight distributing hitch) 4WD: 3855 / 8500; with 5.3L V-8, auto. Trans., 4.10 axle (req. weight distributing hitch)
Ext. Cab, Short Box	2WD: 3629 / 8000; with 5.3L V-8, auto. Trans., 3.73 axle (req. weight distributing hitch) 4WD: 3946 / 8700; with 5.3L V-8, auto. Trans., 4.10 axle (req. weight distributing hitch)
Crew Cab, Short Box	2WD: 4581 / 10100; with 6.0L V-8, auto. Trans., 3.73 axle (req. weight distributing hitch) 4WD: 4491 / 9900; with 6.0L V-8, auto. Trans., 4.10 axle (req. weight distributing hitch)
Crew Cab, Short Box (w/ VortecMAX)	2WD: 4581 / 10100; with 6.0L V-8, auto. Trans., 3.73 axle (req. weight distributing hitch) 4WD: 4445 / 9800; with 6.0L V-8, auto. trans., 4.10 axle (req. weight distributing hitch)
Crew Cab, Std. Box (1500HD)	2WD: 4672 / 10300; with 6.0L V-8, auto. trans., 4.10 axle (req. weight distributing hitch) 4WD: 4491 / 9900; with 6.0L V-8, auto. trans., 4.10 axle (req. weight distributing hitch)

\* 2WD/4WD 1500 Series models limited to 2,250 kg (5,000-pound) trailer ratings unless equipped with Z85 Increased Capacity or ZX3 Manual Select Damping or Z71 Off-Road Suspension Package. Z82 Heavy Duty Trailering Package includes trailer hitch platform, trailer electrical connector and suspension upgrade, if necessary.

## SPECIFICATIONS - SILVERADO 2500HD / 3500 CLASSIC

Engines	Vortec 6000 6.0L V-8 (LQ4)	Vortec 8100 8.1L V-8 (L18)	Duramax 6600 6.6L V-8 (LBZ)
Type:	6.0L V-8	8.1L V-8	6.6L V-8
Displacement (cc / cu in):	5967 / 364	8128 / 496	6599 / 403
Bore & stroke (mm / in):	101.6 x 92 / 4 x 3.62	107.9 x 111 / 4.25 x 4.37	103 x 99 / 4.06 x 3.9
Block material:	Cast iron	Cast iron	Cast iron
Cylinder head material:	Cast aluminum	Cast iron	Cast aluminum
Valvetrain:	OHV	OHV	OHV
Ignition system:	Coil-near-plug, iridium-tipped spark plugs, low-resistance spark plug wires	Coil-near-plug, iridium-tipped spark plugs, low-resistance spark plug wires	Glow plug start aid
Fuel delivery:	Sequential fuel injection	Sequential fuel injection	Direct injection diesel with high pressure common rail
Compression ratio:	9.4:1	9.1:1	16.8:1
Horsepower (hp / kw @ rpm):	300 / 224 @ 4400	330 / 246 @ 4200(L18) 295 / 220 @ 3600 (MD L18 with LRZ option) 242 / 180 @ 3600 (MD L18 with LQR option)	360 / 268 @ 3200 (auto trans)
Torque (lb-ft / Nm @ rpm):	360 / 488 @ 4000	450 / 610 @ 3200 (L18) 440 / 597 @ 3200 (MD L18 with LRZ option) 350 / 475 @ 1200 (MD L18 with LQR option)	650 / 881 @ 1600 (auto trans)
Recommended fuel:	87 octane	87 octane	diesel
Maximum engine speed (rpm):	manual: 5600 auto: 5600	manual: 5000 auto: 4000	3250
Emissions controls:	3-way catalytic converter, exhaust gas recirculation, positive crankcase ventilation, evaporative collection system	3-way catalytic converter, exhaust gas recirculation, positive crankcase ventilation, evaporative collection system	Turbocharged, intercooled, catalytic converter system

[Top ▲](#)

Transmissions	Hydra-Matic 4L80-E	NVG 3500 (MW3)	Allison 1000 (MW7)
Type:	4-speed automatic	5-speed manual	6-speed automatic
<b>Gear ratios (:1):</b>			
First:	2.48	5.61	3.1
Second:	1.48	3.04	1.81
Third:	1.00	1.67	1.41
Fourth:	0.75	1.00	1.00
Fifth:	-	0.75	0.71
Sixth:	-	-	0.61
Reverse:	2.08	5.61	4.49
Final drive ratio (with all transmissions):	Vortec 6000: 4.10 standard on all models Vortec 8100: (opt) 3.73 or 4.10 on 2500HD; 4.10 std on 3500 Series Duramax 6600: 3.73 ratio standard on all models		

## Chassis/Suspension

Front:	All models: std long- and short-arm independent front torsion bar suspension		
Rear:	2500HD Pickups: semi-elliptic 2-stage multileaf spring 3500 Chassis Cabs: 3-stage multileaf spring		
Steering type:	Integral power recirculating ball		
Steering ratio:	24:1		
Steering wheel turns, lock-to-lock:	3.14		
<b>Turning circle, curb-to-curb (m / ft.):</b>	<b>Regular Cab</b>	<b>Extended Cab</b>	<b>Crew Cab</b>
2500HD Series single-wheel pickups:	2WD: 13.4 / 43.8 4WD: 13.4 / 43.8	2WD: 14.3 / 46.8 4WD: 15.5 / 50.8	2WD: 15.1 / 49.6 4WD: 15.1 / 49.6
3500 Series dual-wheel pickups:	2WD: 13.3 / 43.7 4WD: 13.3 / 43.7	2WD: 15.5 / 50.7 4WD: 15.5 / 50.7	2WD: 16.3 / 53.5 4WD: 16.3 / 53.5
3500 Series single-wheel pickups:	4WD: 13.4 / 43.8	4WD: 15.5 / 50.8	4WD: 15.1 / 49.6

## Brakes

Type:	Power, Hydroboost brake-apply system, 4-wheel disc, 4-wheel ABS	
Rotor diameter x thickness (mm / in):	front: 325 x 38 / 12.8 x 1.5 rear: 325 x 30 / 12.8 x 1.2	
Total swept area (sq. cm / sq in.):	front: 1584 / 245.5 rear: 1517 / 235.1	

## Wheels/Tires

Wheel size and type:	8-bolt 16 x 6.5-inch steel wheels std; opt on 2500HD models: chrome centre cap, chrome steel wheels with chrome centre cap and polished forged aluminum wheels Chassis Cab wheels redesigned to display more surface area and provide increased corrosion resistance (compared to previous designs)
Tires:	2500HD models: LT245/75R16E radials, with either all-season or on-/off-road design, depending on model 3500-Series: LT215/85R16-E highway or on-/off-road tires; tire size and inflation pressure geared to specific load ratings

Exterior Dimensions	2500HD / 3500 Regular	2500HD Extended Cab	2500HD / 3500 Extended
	Cab Long Box	Standard Box	Cab Long Box
Wheelbase (mm / in):	3378 / 133	3645 / 143.5	4001 / 157.5
Overall length (mm / in):	2WD: 5641 / 222.1 4WD: 5641 / 222.1	2WD: 5784 / 227.7 4WD: —	2WD: 6264 / 246.6 4WD: 6264 / 246.6
Overall width (mm / in):	2WD: 2024 / 79.7 4WD: 2441 / 96.1	2WD: 2024 / 79.7 4WD: —	2WD: 2024 / 79.7 4WD: 2441 / 96.1
Overall height: (mm / in):	2WD: 2500HD: 1935 / 76.2 3500: 1948 / 76.7 4WD: 2500HD: 1943 / 76.5 3500: 1948 / 76.7	2WD: 1935 / 76.2 - 4WD: 1943 / 76.5 -	2WD: 2500HD: 1935 / 76.2 3500: 1938 / 76.3 4WD: 2500HD: 1943 / 76.5 3500: 1948 / 76.7
Track (mm / in):	front: 1742 / 68.6 rear: 2500HD: 1676 / 66 3500: 1897 / 74.7	front: 1742 / 68.6 rear: 1676 / 66	front: 1742 / 68.6 rear: 2500HD: 1676 / 66 3500: 1897 / 74.7
<b>Minimum ground clearance (mm / in):</b>			
2WD (front):	2500HD: 218.4 / 8.6 3500: 223.5 / 8.8	216 / 8.5	2500HD: 216 / 8.5 3500: 221 / 8.7
2WD (rear):	2500HD: 190.5 / 7.5 3500: 193 / 7.6	188 / 7.4	2500HD: 188 / 7.4 3500: 190.4 / 7.5
4WD (front):	2500HD: 226.1 / 8.9 3500: 223.5 / 8.8	223.5 / 8.8	2500HD: 223.5 / 8.8 3500: 223.5 / 8.8
4WD (rear):	2500HD: 190.5 / 7.5 3500: 193 / 7.6	188 / 7.4	2500HD: 188 / 7.4 3500: 193 / 7.6
<b>Step-in height (mm / in):</b>			
2WD:	2500HD: 632.5 / 24.9 3500: 645.2 / 25.4	619.8 / 24.4	2500HD: 619.8 / 24.4 3500: 632.5 / 24.9
4WD:	2500HD: 645.2 / 25.4 3500: 632.5 / 24.9	624.8 / 24.6	2500HD: 624.8 / 24.6 3500: 632.5 / 24.9
<b>Exterior (cont'd)</b>	<b>2500HD Crew Cab</b>	<b>2500HD / 3500 Crew Cab</b>	
	<b>Standard Box</b>	<b>Long Box</b>	
Wheelbase (mm / in):	3886 / 153	4242 / 167	
Overall length (mm / in):	2WD: 6027 / 237.3 4WD: 6027 / 237.3	2WD: 6507 / 256.2 4WD: 6507 / 256.2	
Overall width (mm / in):	2WD: 2024 / 79.7 4WD: 2024 / 79.7	2WD: 2024 / 79.7 4WD: 2024 / 79.7	
Overall height: (mm / in):	2WD: 77.0 / 1956 4WD: 77.4 / 1966	2WD: 2500HD: 1956 / 77 3500: 1938 / 76.3 4WD: 2500HD: 1956 / 77 3500: 1948 / 76.7	
Track (mm / in):	front: 1742 / 68.6 rear: 1676 / 66.0	front: 1742 / 68.6 rear: 2500HD: 1676 / 66 3500: 1897 / 74.7	
<b>Minimum ground clearance (mm / in):xxx</b>			
2WD (front):	221 / 8.7	2500HD: 221 / 8.7 3500: 221 / 8.7	
2WD (rear):	188.0 / 7.4	2500HD: 193 / 7.6 3500: 193 / 7.6	
4WD (front):	226.1 / 8.9	2500HD: 221 / 8.7 3500: 223.5 / 8.8	
4WD (rear):	188 / 7.4	2500HD: 193 / 7.6 3500: 193 / 7.6	
<b>Step-in height (mm / in):</b>			
2WD:	624.8 / 24.6	2500HD: 624.8 / 24.6 3500: 632.5 / 24.9	
4WD:	631.5 / 25.1	2500HD: 637.5 / 25.1 3500: 632.5 / 24.9	



	<b>GVWR (kg / lb)</b>	<b>Curb Weight (kg / lb)</b>	<b>Payload (kg / lb)</b>	<b>Weight Distribution (% front/rear)</b>
2500HD Reg Cab, Long Box 2WD/4WD:	2WD: 4173 / 9200 4WD: 4173 / 9200	2332 / 5142 2448 / 5398	1841 / 4058 1724 / 3802	56.2 / 43.8 57.8 / 42.2
2500HD Ext Cab, Std. Box 2WD/4WD:	2WD: 4173 / 9200 4WD: 4173 / 9200	2448 / 5398 2567 / 5659	1724 / 3802 1606 / 3541	56.1 / 43.9 58.6 / 41.4
2500HD Ext Cab, Long Box 2WD/4WD:	2WD: 4173 / 9200 4WD: 4173 / 9200	2522 / 5561 2653 / 5848	1651 / 3639 1520 / 3352	56.3 / 43.7 57.9 / 41.1
2500HD Crew Cab, Std. Box 2WD/4WD:	2WD: 4173 / 9200 4WD: 4173 / 9200	2537 / 5594 2668 / 5883	1536 / 3606 1505 / 3317	55.2 / 44.8 57 / 43
2500HD Crew Cab, Long Box 2WD/4WD:	2WD: 4173 / 9200 4WD: 4173 / 9200	2606 / 5745 2738 / 6037	1568 / 3455 1435 / 3163	55.5 / 44.5 57.2 / 42.8
3500 Reg Cab, Long Box, 4WD; SRW / DRW:	SRW: 4491 / 9900 DRW: 5171 / 11400	2580 / 5687 2671 / 5889	1911 / 4213 2500 / 5511	55.5 / 44.5 53.6 / 46.4
3500 Ext Cab, Long Box, 2WD; DRW:	5171 / 11400	2746 / 6053	2425 / 5347	52.3 / 47.7
3500 Ext Cab, Long Box, 4WD; SRW / DRW:	SRW: 4491 / 9900 DRW: 5171 / 11400	2811 / 6197 2881 / 6351	1680 / 3703 2290 / 5049	55.2 / 44.8 53.9 / 46.1
3500 Crew Cab, Long Box, 2WD; DRW:	5171 / 11400	2826 / 6231	2345 / 5169	51.9 / 48.1
3500 Crew Cab, Long Box, 4WD; SRW / DRW:	SRW: 4491 / 9900 DRW: 5171 / 11400	2868 / 6322 2988 / 6552	1623 / 3578 2199 / 4848	55.4 / 44.6 53.6 / 46.4

<b>Cargo box</b>	<b>Long Box</b>	<b>Standard Box</b>
Cargo volume (L / cu ft):	2002 / 70.7	1611 / 56.9
Length at floor (mm / in):	2479 / 97.6	1999 / 78.7
Width at floor (mm / in):	1646 / 64.8	1646 / 64.8
Opening width rear at top (mm / in):	1572 / 61.9	1572 / 61.9
Width between wheel housings (mm / in):	1270 / 50	1270 / 50
Inside height (mm / in):	495 / 19.5	495 / 19.5

<b>Interior Dimensions</b>	<b>Regular Cab</b>	<b>Extended Cab</b>	<b>Crew Cab</b>
Headroom (mm / in):	1041 / 41	front: 1041 / 41 rear: 9753 / 8.4	front: 1041 / 41 rear: 991 / 39
Legroom (mm / in):	1049 / 41.3	front: 1049 / 41.3 rear: 856 / 33.7	front: 1049 / 41.3 rear: 993 / 39.1
Shoulder room (mm / in):	1656 / 65.2	front: 1656 / 65.2 rear: 1684 / 66.3	front: 1656 / 65.2 rear: 1654 / 65.1
Hip room (mm / in):	1560 / 61.4	front: 1560 / 61.4 rear: 1562 / 61.5	front: 1560 / 61.4 rear: 1598 / 62.9

## Capacities

Fuel tank (L / imp.gal):	Standard box, all models (except diesel): 98.4 / 26; Long box, all models (plus all diesels): 128.7 / 34; DRW chassis cab: 189.3 / 50
<b>Trailer towing maximum (kg / lb):</b>	
2500HD Reg. Cab, Long Box:	2WD: 5443 / 12000; 8.1L V-8 (w/4.10 axle) or 6.6L Diesel (w/3.73 axle); 4WD: 5443 / 12000; 8.1L V-8 (w/4.10 axle) or 6.6L Diesel (w/3.73 axle)
2500HD Ext. Cab, Std. Box:	2WD: 5443 / 12000; 8.1L V-8 (w/4.10 axle) or 6.6L Diesel (w/3.73 axle); 4WD: 5443 / 12000; 8.1L V-8 (w/4.10 axle) or 6.6L Diesel (w/3.73 axle);
2500HD Ext. Cab, Long Box:	2WD: 5443 / 12000; 8.1L V-8 (w/4.10 axle) or 6.6L Diesel (w/3.73 axle) 4WD: 5443 / 12000; 8.1L V-8 (w/4.10 axle) or 6.6L Diesel (w/3.73 axle)
2500HD Crew Cab, Std. Box:	2WD: 5443 / 12000; 8.1L V-8 (w/4.10 axle) or 6.6L Diesel (w/3.73 axle) 4WD: 5443 / 12000; 8.1L V-8 (w/4.10 axle) or 6.6L Diesel (w/3.73 axle)
2500HD Crew Cab, Long Box:	2WD: 5443 / 12000; 8.1L V-8 (w/4.10 axle) or 6.6L Diesel (w/3.73 axle) 4WD: 5443 / 12000; 8.1L V-8 (w/4.10 axle) or 6.6L Diesel (w/3.73 axle)
3500 Reg. Cab, Long Box, 4WD; SRW / DRW:	SRW: 5443 / 12000; 8.1L V-8 (w/4.10 axle) or 6.6L Diesel (w/3.73 axle) DRW: 5443 / 12000; 8.1L V-8 (w/4.10 axle) or 6.6L Diesel (w/3.73 axle)
3500 Ext. Cab, Long Box, 2WD; DRW	DRW: 5443 / 12000; 8.1L V-8 (w/4.10 axle) or 6.6L Diesel (w/3.73 axle)
3500 Ext. Cab, Long Box, 4WD; SRW / DRW:	SRW: 5443 / 12000; 8.1L V-8 (w/4.10 axle) or 6.6L Diesel (w/3.73 axle) DRW: 5443 / 12000; 8.1L V-8 (w/4.10 axle) or 6.6L Diesel (w/3.73 axle)
3500 Crew Cab, Long Box, 2WD; DRW:	DRW: 5443 / 12000; 8.1L V-8 (w/4.10 axle) or 6.6L Diesel (w/3.73 axle)
3500 Crew Cab, Long Box, 4WD; SRW / DRW:	SRW: 5443 / 12000; 8.1L V-8 (w/4.10 axle) or 6.6L Diesel (w/3.73 axle) 4WD: 5443 / 12000; 8.1L V-8 (w/4.10 axle) or 6.6L Diesel (w/3.73 axle)

\* For alternative-fuel vehicles, trailer tongue weight should be 10 to 15 percent of total-loaded trailer weight. On other models, trailer tongue weight should be 10 to 15 percent of total-loaded trailer weight up to 1,500 lb. (675 kg). On all models, the base cooling system includes all content required to attain maximum trailering rating, and the Z82 Heavy Duty trailering package includes the trailer hitch platform and trailer electrical connector.

	Regular Cab	Extended Cab	Crew Cab
Seating:	2 / 3	5 / 6	5 / 6

OnStar® OnStar services require vehicle electrical system (including battery), wireless service and GPS satellite signals to be available and operating for features to function properly. OnStar acts as a link to existing emergency service providers. Subscription Service Agreement required. OnStar Hands-free Calling requires a Hands-Free Calling enabled vehicle, existing OnStar service contract and prepaid minutes or enrollment in a shared minute plan. Not available in certain markets. Calls may be made to the U.S. and Canada only. OnStar voice recognition system may not work with some voices. Due to the transition of the wireless industry from analogue to digital technology, as of January 1, 2008, OnStar plans to offer service only through equipment that operates on the digital network, which may require the purchase of a system upgrade for eligible vehicles. Call 1-888-4ONSTAR (1-888-466-7827) or visit onstar.ca for OnStar's Terms and Conditions, Privacy Policy and system limitations and details.

© 2006 OnStar Corporation. All rights reserved. OnStar and the OnStar emblem are registered trademarks of OnStar Corporation. The GM emblem is a registered trademark of the GM Corporation.